



## »» 矿山设备（制砂）系统 解决方案服务商

MINING EQUIPMENT (SAND MAKING) SYSTEM  
SOLUTIONS PROVIDER

[www.cementcrusher.com](http://www.cementcrusher.com)



### 河南省振源科技有限公司

Henan Zhenyuan Science & Technology Co.,Ltd.

Add: Xiaodian Industrial Park, Xinxiang, Henan

Tel: +86-373-3663336 +86-373-3663285

Fax: +86-373-3663296

Email: [info@cementcrusher.com](mailto:info@cementcrusher.com)

Website: [www.cementcrusher.com](http://www.cementcrusher.com)

### 河南省振源科技有限公司

Henan Zhenyuan Science & Technology Co.,Ltd.





专心·专注·专业  
ATTENTIVELY ABSORBED PROFESSIONAL



## 公司介绍



河南省振源科技有限公司，是专业从事矿用机械设备的国家级高新技术企业，主要产品有：移动破碎站、制砂机、洗砂机、各种破碎机、振动筛、给料机及相关配件等。产品广泛应用于矿山、碎石、制砂、选矿等行业，远销东南亚、南亚等地区。凭着质量过硬的产品和周到的服务，积累了良好的市场信誉，并获得了广大客户的信任和好评。

地处黄河之北岸，国家新乡经济技术开发区，占地面积260亩，建筑面积10.9万平米。公司现有员工690人，其中行业专家3名，高级技术人员80人，中级技术人员120人，公司总资产4.38亿元。

公司拥有科学的质量管理体系和先进的产品质量检测手段，在同行业率先通过了ISO9001质量管理体系认证，产品质量始终保持同行业领先水平。公司拥有三十余项国家专利，曾多次荣获国家、省部级科技奖。

以“不断创新、服务至上、笃守信誉”为企业宗旨；以“创世界一流产品”为己任。公司坚持以市场为导向，以顾客满意为目的，追求卓越绩效并持续改进，以一流的产品，一流的服务创一流的业绩。热烈欢迎各界人士精诚合作，共同创造辉煌的明天，实现和谐共赢！

## Company Introduction



Henan Zhenyuan Science & Technology Co.,Ltd. is a hi-tech enterprise specializing in manufacturing nonferrous metals and coal mining machine, Our main products include:crusher plant, sand making machine , sand washer, crusher, vibrating screen, vibrating feeder, which are widely used in coal, metallurgy, mine, electricity, chemical industry etc. Our products are exported to Southeast Asian countries, South Asian and other countries.We gained favorable comment and trust from customers with our high quality products and considerate service, winning buyer praise in the market.

Located on the north bank of the Yellow River, east of Xinxiang City,Our company occupies an area of 109,000.00 square meters, with 690 staffs, among which there are 3 specialists, 80 senior technicians and 120 middle class technicians, and capital asset ¥438.000.000.

We have scientific QC system and passed the ISO9001 quality control system, firstly among fellow companies. With advanced quality testing methods, our products in the industry has maintained the top level. More than 30 national patents have been awarded,and many science and technology prizes have been awarded by State and Provincial governments.

We abide by“ Unceasing innovation, excellent service, keeping reputation”, and always take the market as a guide, trying our best to satisfy customers, pursue super excellence and insist on continual improvement. To create prominent achievement with first-class products and first-class service. We are sincerely hope to cooperate with friends from home and abroad to create a glorious tomorrow and realize our common aim of “Harmony and Win-win”!





## IMPROVER THE QUALITY SERVE THE WORLD

With high quality products and considerate service, our products have been exported to Southeast Asia, South Asia and other countries and regions, and continue to extend to the rest of the world in Africa, Europe, also establishing longterm and full cooperation, common development, hand in hand and winwin. We will always adhere to the ideas, enthusiastic attitude and integrity is reflected in presale, sale, aftersale services centers, and foreign sales service centers, technical centers, multilevel, multinetwork of fast and convenient service network, the product is worth the additional value to maximize, to show the world China power.

## 提升品质 服务全球

凭着质量过硬的产品和周到的服务，公司产品已经远销东南亚、南亚等国家和地区，并不断延伸至非洲、欧洲等世界各地，建立长期、全面的合作关系，共同发展，携手共赢。我们将坚持一贯的理念，以热情和诚信的态度体现于售前、售中、售后服务全过程，驻外销售服务中心、技术中心等多层次、多网点的快速便捷服务网络，使产品附加值得到最大化，向世界展示中国力量。



印度尼西亚客户



意大利客户



俄罗斯客户



越南客户



土耳其客户



意大利·达涅利集团客户



阿尔及利亚客户





## 资质荣誉 Qualification Honors



## 加工设备 Product Equipments



龙门镗床  
Gantry Boring Machine

数显落地铣镗床  
Significant Number Of Boring  
And Milling Machine

抛丸机  
Shot Blasting Machine



大型立车  
Heavy Duty Vertical Lathe

大型卧式车床  
Large Horizontal Lathe

大型热处理设备  
Large-scale Heat Treatment Equipment



数控加工区  
CNC Processing Area

龙门铣床  
Gantry Boring And

数控等离子切割机  
NC Plasma Cutting Machine



## DMC型脉冲袋式除尘器

DMC PULSE BAG DUST CATCHER



DMC型脉冲单机袋式除尘器是一种成熟的比较完善的高效除尘设备，具有处理风量大、占地面积小、净化效率高、工作可靠、结构简单、维修量小等特点，除尘效率可以达到99%以上。

DMC Pulse Bag Dust Catcher of Zhenyuan Technology is a kind of mature high efficiency dust removing-cleaning plant, which has characters like large air flow, small footprint, high efficiency of purification, reliable working performance, simple structure and easy to maintain. It is worth mentioning that Zhenyuan Technology dust collection efficiency can reach to 99%.

### 规格与性能参数表 / SPECIFICATION AND TECHNICAL PARAMETER

型号 Model	处理风量(m <sup>3</sup> /min) Airflow	过滤面积(m <sup>2</sup> ) Filter area	风速(m/min) Air speed	滤袋规格Model(mm) Filter bag size	滤袋数量(个) Filter bag qty	脉冲阀(个) Pulse valve	风机+卸料+螺旋(kw) Motor power(blower+discharge+screw)
DMC-80	12000~16800	80	2.5~3.5	φ130×2500	80	10	15+0.75
DMC-104	15600~21840	104	2.5~3.5	φ130×2500	104	13	15+0.75+4
DMC-120	18000~25200	120	2.5~3.5	φ130×2500	120	15	22+0.75+4
DMC-160	24000~33600	160	2.5~3.5	φ130×2500	160	20	37+0.75+4
DMC-184	27600~38640	184	2.5~3.5	φ130×2500	184	23	37+0.75+4
DMC-200	30000~42000	200	2.5~3.5	φ130×2500	200	25	37+0.75+4
DMC-224	33600~47040	224	2.5~3.5	φ130×2500	224	28	37+0.75+4
DMC-264	39600~55440	264	2.5~3.5	φ130×2500	264	33	55+0.75+4
DMC-304	45600~63840	304	2.5~3.5	φ130×2500	304	38	55+0.75+4





**规格与性能参数表 / SPECIFICATION AND TECHNICAL PARAMETER**

设备名称 Name	规格型号 Model	产量(t/h) capacity	参考风量(m <sup>3</sup> /h) Air volume	参考风压 (Pa) Air pressure	排尘量(t/h) Dust discharge	吸尘罩面积及位置 Dust Hood Area and Position
颚式破碎机 Jaw Crusher	PE600×900	60-160	4500-6000	7610-6527	0.3-0.6	1000×1200 下吸尘 below
	PE750×1060	90-320	4500-6000	1800-1200	0.3-0.6	1200×1500 下吸尘 below
	PE900×1200	140-450	4500-6000	1800-1200	0.5-0.8	1200×1500 下吸尘 below
	PE1000×1200	160-550	4500-8000	1800-1200	0.5-0.8	1400×1500 下吸尘 below
	PE1200×1500	400-800	4500-8000	1800-1200	0.6-1.0	1500×1500 下吸尘 below
反击破碎机 Impact Crusher	PF-1007	35-50	4500-8000	1800-1200	0.5-1.0	700×1000 下吸尘 below
	PF-1010	50-80	6000-10000	1800-1200	0.5-1.0	700×1000 下吸尘 below
	PF-1210	70-120	8000-10000	1800-1200	0.5-1.0	1000×1200 下吸尘 below
	PF-1214	80-160	8000-10000	1800-1200	0.5-1.0	1000×1200 下吸尘 below
	PF-1315	90-220	10000-12000	1800-1200	0.5-1.5	1200×1500 下吸尘 below
圆锥破碎机 Cone Crusher	PY-900	15-90	4500-8000	1800-1200	0.3-0.6	700×1000 下吸尘 below
	PY-1200	18-168	4500-8000	1800-1200	0.3-0.6	1000×1200 下吸尘 below
	PY-1750	75-480	8000-10000	1800-1200	0.5-0.8	1200×1500 下吸尘 below
	PY-2200	120-1000	10000-12000	1800-1200	0.5-1.0	1400×1500 下吸尘 below
制砂机 Sand Making Machine	PCL600	12-30	8000-10000	1800-1200	0.3-0.6	700×1000 下吸尘 below
	PCL750	26-65	8000-10000	1800-1200	0.4-0.7	700×1000 下吸尘 below
	PCL900	55-120	10000-13000	1800-1200	0.4-0.8	700×1000 下吸尘 below
	PCL1050	90-160	10000-15000	1800-1200	0.4-0.8	1000×1200 下吸尘 below
	PCL1250	100-260	12000-18000	1800-1200	0.5-1.0	1000×1200 下吸尘 below
	PCL1350	160-360	13000-21000	1800-1200	0.5-1.5	1200×1500 下吸尘 below
圆振动筛 Circular Vibrating Screen	3YA1237	10-80	10000-13000	1800-1200	0.3-0.6	1200×3700 上吸尘 upper
	3YA1548	22-160	10000-15000	1800-1200	0.4-0.7	1500×4800 上吸尘 upper
	3YA1848	32-276	12000-18000	1800-1200	0.4-0.8	1800×4800 上吸尘 upper
	3YA1860	65-586	12000-18000	1800-1200	0.4-0.8	1800×6000 上吸尘 upper
	3YA2160	81-720	13000-21000	1800-1200	0.5-1.0	2100×6000 上吸尘 upper
	3YA2460	90-810	13000-21000	1800-1200	0.5-1.5	2400×6000 上吸尘 upper

## 胶带输送机

 BELT CONVEYOR


我公司生产的胶带输送机输送量大，结构简单，维修方便，部件标准化。用于输送松散物料或成件物品，广泛应用于矿山、煤炭和冶金等行业。根据输送工艺要求，可单台输送，也可多台组成输送系统，或与其他输送设备组成水平或倾斜的输送系统，以满足不同形式的作业线需求。

The advantages of our Belt Conveyor are: high capacity, simple structure, easy maintenance, standard spare parts. According to the different demands, the transfer system can be one independently or multi-conveyors or combined with other transfer equipments. The belt conveyor can be installed horizontally or aslope to meet the needs of different transfer lines.

**规格与性能参数表 / SPECIFICATION AND TECHNICAL PARAMETER**

胶带宽度 (毫米) Belt Width(mm)	输送长度 (米) / 功率 (千瓦) Belt Length(m)/Power(kw)		输送速度 (米/秒) Belt Speed(m/s)	输送量 (吨/小时) Capacity(t/h)
400	≤12/1.5	12-20/2.2	20-25/3	40-80
500	≤12/3	12-20/4	20-30/5.5	78-191
650	≤12/4	12-20/5.5	20-30/7.5	131-323
800	≤10/4	10-15/5.5	15-25/7.5	278-546
1000	≤10/5.5	10-20/7.5	20-25/11	435-853
1200	≤10/7.5	12-20/11	20-25/15	655-1284